

# THE GLOBAL SPECIALIST FOR PVC COMPOUNDS

## DATA SHEET

### norvinyl® GA.54.10.00798

<b>Description</b>	Flexible PVC Extrusion Compound
<b>Colour</b>	Natural
<b>Application</b>	Profiles
<b>Compliances</b>	REACH Regulations 1907/2006 and 2011/10/EC (RoHS)
<b>Form</b>	Pellets
<b>SDS No.</b>	

## TYPICAL PROPERTIES

	Test Method	Units	Value
<b>General Properties</b>			
Density (varies with colour)	EN ISO 1183-1A	g/cm <sup>3</sup>	1,187 ±0,01
Hardness (15 sec@23°C)	EN ISO/R 868	Shore A	54 ±2
<b>Other Properties</b>			
Cold Flex	EN ISO 458	°C	-25
Thermal Stability	EN ISO 182-1	Min	60

\*Material tested on extruded profile. Actual performance may vary depending upon product design. Customers are advised to verify product as required.

Issue 30 October 2018

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given, nor is to be implied with respect of such information. Users should make their own enquiries to determine the suitability of products for any particular application. Freedom from patents, copyright and registered designs cannot be determined.

#### INEOS Compounds Aycliffe Limited

School Aycliffe Lane  
Newton Aycliffe  
Co. Durham DL5 6EA  
United Kingdom

Tel: +44 (0) 1325 300555  
Fax: +44 (0) 1325 303001

#### INEOS Compounds Sins, Switzerland

INEOS Compounds Switzerland AG  
Industrie Nord 2  
CH-5643 Sins  
Switzerland

Tel: +41 41 78 98 200  
Fax: +44 41 78 98 234

#### INEOS Compounds Helsingborg, Sweden

INEOS Compounds Sweden AB  
Gevärsgatan 4  
SE-254 66 Helsingborg  
Sweden

Tel: +46 42 250 200  
Fax: +46 42 250 280

**INEOS**  
Compounds

www.ineos.com