



# Solid reasons for Vinyl flooring with SPC core board




**Particularly dimensionally stable**  
Can be installed in large rooms without expansion joints (max. 400m<sup>2</sup>, 20 x 20 m)



**For demanding room situations**  
Can be installed in front of floor-to-ceiling windows and in conservatories



**Suitable for underfloor heating**



**Installation-friendly**  
Comfort-Click System for straightforward, safe and custom-fit installation



**Wear classes**  
WC 23/WC 31 (Wear layer 0.3 mm)



**Warranty terms**  
10 years

**Product structure**

- ① UV coating layer
- ② Vinyl wear layer
- ③ Vinyl decor layer
- ④ SPC core layer (SPC = Solid Polymer Core)
- ⑤ Acoustic counter layer
- ⑥ Comfort Click System

Please comply with the installation and care instructions in the advice section available at [www.parador.eu](http://www.parador.eu)

**Made in Germany**  
Tested and healthy living

**100% waterproof for universal use**  
Also perfect for use in areas subject to moisture like kitchens, bathrooms, etc.

**Particularly quiet and warm underfoot**  
Resilient surface in combination with the acoustic counter layer ensures walking and living comfort

**Integrated acoustic counter layer**  
Ensures optimum room acoustics and minimizes noise


**Robust and easy to maintain**  
Ideal for all everyday situations

**Antibacterial and hygienic**  
Resists dirt and bacteria

**Large plank format with 4-sided bevel**  
1209 x 225 x 5.3 mm

**Suitable for slightly uneven substrates**  
Ideal for renovations; can also be installed on existing tiles

**Installation over joints and through doors**  
Without expansion joints across construction and screed joints



Made in Germany  
Certified  
Healthy living  
[www.parador.de](http://www.parador.de)

# PARADOR

## Product features Basic 5.3

- **Water-resistant**
- **Particularly dimensionally stable**  
Installation in conservatories and in front of floor-to-ceiling windows
- **Integrated footfall sound insulation**
- **Suitable for slightly uneven substrates**  
Tile joints max. 8 mm wide, 2 mm deep
- **Quiet and warm underfoot**
- **Robust and low-maintenance**
- **Antibacterial and hygienic**
- **Suitable for underfloor heating**
- **Installation-friendly thanks to Comfort Click System**
- **Low installation height**
- **Renovation-friendly**
- **Installation in large rooms possible**  
**max. 400 m<sup>2</sup>, 20 x 20 m**
- **Seamless installation across rooms without expansion joints**
- **Made in Germany**